

floors@home/20

floors@home/30

Covering type according to ISO 10582	Heterogeneous Planks / Tiles, type 1	
Number of colours	30 planks	58 planks / 22 tiles
Packaging per box/pallet	3.34 m <sup>2</sup> /240.48 m <sup>2</sup> 600x600 mm: 3.24 m <sup>2</sup> /233.28 m <sup>2</sup>	
Performance classification EN ISO 10582 / ISO 10874	22	23, 31
Total thickness ISO 24346	2.0 mm	
Wearlayer thickness ISO 24340	0.2 mm	0.3 mm
Surface treatment	ja/PU	
Bevelled edges	nein	ja (dekorabhängig)
Total weight ISO 23997	3.20 kg/m <sup>2</sup>	3.51 kg/m <sup>2</sup>
Residual indentation ISO 24343-1	≤ 0.1 mm*	
Dimensional stability ISO 23999	≤ 0.15 %*	
Castor chair suitability ISO 4918	yes – using EN 12529, type W	
Underfloor heating EN 1264-2	suitable up to 28°C	
Behaviour to fire EN 13501-1	Bfl-s1	
Resistance to thermal conductivity ISO 8302/ EN 12667	0.02 m <sup>2</sup> K/W	
Electrical propensity when walked upon EN 1815	< 2 kV	
Impact sound improvement ISO 10140-3	2 dB	
Colour fastness to artificial light ISO 105-B02/02	≥ 7	
Electrostatic characteristics EN 1081	> 10 <sup>12</sup>	
Chemical resistance ISO 26987	conforms**	
Slip resistance	R9 to R10 (depending on design resp. emboss: details available on request)	
Adhesive recommendation	see installation instruction	
Maintenance/Cleaning recommendation	Dr. Schutz	

\* Averaged value

(Date: 01/01/2023)

\*\* Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions.

