

Technical Data CLICK COLLECTION

PROJECT FLOORS

CLICK COLLECTION/30

CLICK COLLECTION/55

Covering type in accordance with EN ISO 10582	Heterogeneous Planks / Tiles, Type 1	
Number of colours	24 Planks / 8 Tiles	
Pack. Unit/Pallet	1220x180 mm: 1.76 m ² /84.48 m ² 906x448 mm: 2.03 m ² /68.99 m ² 803x398 mm: 1.92 m ² /57.54 m ²	
Performance classification EN ISO 10582 / ISO 10874	23, 31	23, 33
Total thickness ISO 24346	5.0 mm	
Wear layer thickness ISO 24340	0.3 mm	0.55 mm
Surface treatment	yes/PU	
Bevelled edges	yes	
Total weight ISO 23997	10.28 kg/m ²	10.40 kg/m ²
Residual indentation ISO 24343-1	≤ 0.1 mm*	
Dimensional stability ISO 23999	≤ 0.15 %*	
Castor chair suitability ISO 4918	yes – using EN 12529, Type W	
Underfloor heating EN 1264-2	suitable up to 28°C	
Behaviour to fire EN 13501-1	Bfl-s1	
Resistance to thermal conductivity ISO 8302 / EN 12667	0.02 m ² K/W	
Electrical propensity when walked upon EN 1815	< 2 kV	
Impact sound improvement ISO 10140-3	9 dB	
Colour fastness to artificial light ISO 105-B02/02	≥ 7	
Tensile strength of fixings prEN ISO 10582, appendix D	long side ≥ 4.5 kN/m, short side ≥ 5.5 kN/m	
Electrostatic characteristics EN 1081	> 10 ¹²	
Chemical resistance ISO 26987	conforms**	
Slip resistance	R10	
Maintenance/Cleaning recommendations:	Dr. Schutz	

* Averaged value

(Date: 01.01.2020)

** Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions.

