

Technical Data

Herringbone planks



PROJECT

FLOORS

Covering type according to EN ISO 10582	Heterogeneous Planks, Type 1
Number of colours	10 planks
Dimensions of Planks	457x76x2.5 mm and 610x102x2.5 mm
Packaging per box/pallet	3.34 m ² /200.40 m ²
Performance classification EN ISO 10582 / ISO 10874	23, 33, 42
Total thickness ISO 24346	2.5 mm
Wearlayer thickness ISO 24340	0.55 mm
Surface treatment	yes/PU
Bevelled edges	Yes
Total weight ISO 23997	3.81 kg/m ²
Residual indentation ISO 24343-1	≤ 0.1 mm*
Dimensional stability ISO 23999	≤ 0.15%*
Castor chair suitability ISO 4918	yes – using EN 12529, Typ W
Underfloor heating EN 1264-2	suitable up to 28°C
Behaviour to fire EN 13501-1	Bfl-s1
Resistance to thermal conductivity ISO 8302 / EN 12667	0.02 m ² K/W
Electrical propensity when walked upon EN 1815	< 2 k/V
Impact sound improvement ISO 10140-3	4 dB
Colour fastness to artificial light ISO 105-B02/2	≥ 7
Electrostatic characteristics EN 1081	> 10 ¹²
Chemical resistance ISO 26987	conforms**
Slip resistance	R9 to R10 (depending on design resp. emboss: details available on request)
Adhesive recommendation	see installation instruction
Maintenance/Cleaning recommendation	Dr. Schutz

* Averaged value

(Date: 01.01.2023)

** Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions.

